



Fluid Loss Control Agents & Dispersants

AUS-TEX

Description

AUS-TEX is sodium asphalt sulphonate, and is 80% - 90% soluble in both fresh and hard water. When mixed in the mud system it coats out on the hole wall and assists with lubricity, shale stabilization and water loss. It also assists in the prevention of differential sticking.

Application

AUS-TEX can be used in all types of drilling applications - diamond coring, mud rotary and oil wells. It provides lubricity in hard water environments where conventional lubrication products cannot be used.

Advantages

- Provides drill rod lubricity in diamond drilling operations.
- Provides drill rod lubricity in diamond drilling operations.
- Coats out on the hole to assist with shale/clay control.
- Excellent general-purpose mud conditioner.

Usage

AUS-TEX should be mixed through a mud hopper at between 5 to 15kgs per 1,000 litres. When using in hard water, pre-mixing with fresh water will enhance performance.

Packaging

AUS-TEX is packaged in 25 kg sacks.



Head Office

5 Pitino Court, Osborne Park, Western Australia 6017

Tel +61 (0) 8 9445 4000 Fax: +61 (0) 8 9445 4040

amc@imdexlimited.com

www.ausmud.com

AMC has some 50 stock points within Australia and 80 throughout the world including Asia, Africa, the Americas and Europe.

an **imdex** limited company