



Viscosifiers

AUS-GEL

Description

AUS-GEL is a modified, premium grade sodium bentonite, formulated to ensure ease of mixing and superior mud making qualities in fresh water.

Application

AUS-GEL is recommended as a high yielding viscosifier for building a mud system with excellent hole cleaning properties and low filtrate loss in fresh to brackish water. The product makes an economical, low solids drilling fluid which has specific application in water wells with permeable sections or poorly consolidated caving formations. AUS-GEL yields approximately twice the amount of standard AUS-BEN.

Advantages

- Yields rapidly in fresh water to give high viscosity.
- Economical – single product preparation of a low solids drilling mud.
- Economical - provides a single product preparation for a low solids drilling mud.
- Environmentally friendly - does not ferment and is non-toxic.

Usage

Normal – 15 to 30 kgs/1,000 litres

Unconsolidated, caving formation – 35 to 45 kgs/1,000 litres

Lost circulation – 40 to 55 kgs/1,000 litres

Packaging

AUS-GEL is packaged in 25 kg multi-walled paper bags.



Head Office

5 Pitino Court, Osborne Park, Western Australia 6017

Tel +61 (0) 8 9445 4000 Fax: +61 (0) 8 9445 4040

amc@imdexlimited.com

www.ausmud.com

AMC has some 50 stock points within Australia and 80 throughout the world including Asia, Africa, the Americas and Europe.

an **imdex** limited company