



# Lubricants & Cutting Oils

## AMC-HAMMER OIL (DOWN HOLE HAMMER LUBRICANT)

### Description

AMC-BIODEGRADABLE HAMMER OIL comes in three viscosity grades, 150, 320 and 460 centipoises. All grades are formulated with a tackifier to give the AMC-BIODEGRADABLE HAMMER OIL superior adhesion to metal surfaces.

### Application

AMC-BIODEGRADABLE HAMMER OIL is used in all types of air driven down hole hammers as an air line lubricant.

AMC-BIODEGRADABLE HAMMER OIL is not recommended as a preserving additive when preparing hammer oil for prolonged periods of storage.

### Advantages

- Excellent extreme pressure lubrication - provides wear protection to moving parts operating under extreme pressures and temperatures.
- High operating viscosity - does not reduce viscosity under high temperature and pressure thus retaining effective sealing and optimum performance of the hammer.

- Cost Effective - the excellent extreme pressure lubrication allows reduced injection rates with no reduction in lubrication to the Hammer.
- Excellent adhesion to metal surfaces compared to normal oils without a tackifier.

### Usage

Holes Size From

- 3½" (92mm) to 5' (127mm) - 1.5 - 2.0 litres/hour
- 5" (127mm) to 7½" (190.5mm) - 2.0 - 2.5 litres/hour
- 7½" (190.5mm) to 8½" (215.9mm) - 2.5 - 3.0 litres/hour
- 8½" (215.9mm) to 8¾" (222.25mm) - 3.0 - 3.5 litres/hour
- Larger hole size up to 17½" (44.5mm) - 4.5 - 5.0 litres/hour

### Packaging

AMC-HAMMER OIL is packaged in 25 litre or 205 litre drums.



### Head Office

5 Pitino Court, Osborne Park, Western Australia 6017

Tel +61 (0) 8 9445 4000 Fax: +61 (0) 8 9445 4040

amc@imdexlimited.com

[www.ausmud.com](http://www.ausmud.com)

AMC has some 50 stock points within Australia and 80 throughout the world including Asia, Africa, the Americas and Europe.

an **imdex** limited company